

1	2	3		4	5	6																												
		RevNo	Revision note			Date	Signature	Checked																										
<div style="position: absolute; top: 10px; left: 10px; font-weight: bold; font-size: 1.2em;"> <u>Electrical Properties</u> </div> <table border="1" style="margin: 20px auto; border-collapse: collapse; text-align: center;"> <tr> <td style="width: 40%;">AC input voltage range</td> <td>176-264VAC</td> </tr> <tr> <td>Input frequency</td> <td>47-63HZ</td> </tr> <tr> <td>AC inrush current</td> <td>Cold start, 60A/230VAC</td> </tr> <tr> <td>DC adjustment range</td> <td>± 10% rated output voltage</td> </tr> <tr> <td>Line regulation (full load)</td> <td>≤0.5%</td> </tr> <tr> <td>Output overload protection</td> <td>110%-150% shut off, AC recycle to re-start</td> </tr> <tr> <td>Rise, hold up time</td> <td>50mS, 20mS at full load (typical)</td> </tr> <tr> <td>Dielectric withstand voltage</td> <td>I/P-O/P, I/P-FG: 1.5KVAC, O/P-FG: 0.5KVAC, 1 min</td> </tr> <tr> <td>Working temperature</td> <td>-10 to +40°C @ 100% load, +60°C @ 60% load</td> </tr> <tr> <td>Storage temperature</td> <td>-20°C to +85°C, 20% to 95%RH (non condensing)</td> </tr> <tr> <td>Safety standards</td> <td>Design refer to GB4943, UL60950-1, EN60950-1</td> </tr> <tr> <td>EMC standards</td> <td>Design refer to GB9254, EN55022 class A</td> </tr> <tr> <td>Cooling method</td> <td>Forced air cooling by Built-in DC fan</td> </tr> </table>									AC input voltage range	176-264VAC	Input frequency	47-63HZ	AC inrush current	Cold start, 60A/230VAC	DC adjustment range	± 10% rated output voltage	Line regulation (full load)	≤0.5%	Output overload protection	110%-150% shut off, AC recycle to re-start	Rise, hold up time	50mS, 20mS at full load (typical)	Dielectric withstand voltage	I/P-O/P, I/P-FG: 1.5KVAC, O/P-FG: 0.5KVAC, 1 min	Working temperature	-10 to +40°C @ 100% load, +60°C @ 60% load	Storage temperature	-20°C to +85°C, 20% to 95%RH (non condensing)	Safety standards	Design refer to GB4943, UL60950-1, EN60950-1	EMC standards	Design refer to GB9254, EN55022 class A	Cooling method	Forced air cooling by Built-in DC fan
AC input voltage range	176-264VAC																																	
Input frequency	47-63HZ																																	
AC inrush current	Cold start, 60A/230VAC																																	
DC adjustment range	± 10% rated output voltage																																	
Line regulation (full load)	≤0.5%																																	
Output overload protection	110%-150% shut off, AC recycle to re-start																																	
Rise, hold up time	50mS, 20mS at full load (typical)																																	
Dielectric withstand voltage	I/P-O/P, I/P-FG: 1.5KVAC, O/P-FG: 0.5KVAC, 1 min																																	
Working temperature	-10 to +40°C @ 100% load, +60°C @ 60% load																																	
Storage temperature	-20°C to +85°C, 20% to 95%RH (non condensing)																																	
Safety standards	Design refer to GB4943, UL60950-1, EN60950-1																																	
EMC standards	Design refer to GB9254, EN55022 class A																																	
Cooling method	Forced air cooling by Built-in DC fan																																	
<table border="1" style="margin: 20px auto; border-collapse: collapse; text-align: center;"> <tr> <td style="width: 10%;">Itemref</td> <td style="width: 10%;">Quantity</td> <td style="width: 40%;">Title/Name, designation, material, dimension etc</td> <td colspan="2" style="width: 40%;">Article No./Reference</td> </tr> <tr> <td colspan="2">Drawn by Cas Jansen</td> <td>Checked by Kevin Damen</td> <td>Approved by - date 12-11-2020</td> <td>File name</td> </tr> <tr> <td colspan="2"></td> <td colspan="3">Date 12-11-2020</td> </tr> <tr> <td colspan="2"></td> <td colspan="3">Scale 1:1</td> </tr> </table> <div style="display: flex; justify-content: space-around; align-items: center; margin-top: 20px;"> <div style="font-size: 3em; font-weight: bold;">202</div> <div style="text-align: right;"> <div style="font-weight: bold; font-size: 1.2em;">www.damencnc.com</div> <div style="display: flex; justify-content: space-between; font-size: 0.8em;"> <span>202    Switching Powersupply 400W 48V 8,3A DC output</span> <span>Edition    Sheet 4 OF 4</span> </div> </div> </div>									Itemref	Quantity	Title/Name, designation, material, dimension etc	Article No./Reference		Drawn by Cas Jansen		Checked by Kevin Damen	Approved by - date 12-11-2020	File name			Date 12-11-2020					Scale 1:1								
Itemref	Quantity	Title/Name, designation, material, dimension etc	Article No./Reference																															
Drawn by Cas Jansen		Checked by Kevin Damen	Approved by - date 12-11-2020	File name																														
		Date 12-11-2020																																
		Scale 1:1																																
1	2	3		4	5	6																												