

ETP HYDRO-GRIP G2



ETP Transmission AB
Roxtorpsgratan 22, Box 1120
581 11 Linköping, Sweden

www.etp.se

ETP Transmission Inc.
135 Furniture Row
Milford, CT 06460, USA



Operating instruction

E-469-1/Leon Norrköping

ETP HYDRO-GRIP G2

Description

The new HYDRO-GRIP G2 is a hydraulic chuck with tough and compact design.

Features

The G2 features a double walled construction and pressurization is carried out with the supplied allen T-wrench. The G2 chuck may be pressurized without a tool inserted although this is not recommended.

Benefits

HYDRO-GRIP G2, offers excellent centering and fastening performance, fantastic user friendliness and very rapid tool changes. Great performance, ease of use and less downtime, all in one unit!

Technical facts

Tolerances

The G2 chuck is designed and manufactured for a router bit shank with the tolerance g6 (h7).

Transmittable torque for tools with tolerances

	h6	h7	g6	Safety screw
D	Nm	Nm	Nm	ISO 4762
12	60	30	30	M6x40
16	100	75	75	M6x40
20	260	175	175	M8x45
25	480	350	350	M8x45
1/2"	60	30	30	M6x40
5/8"	100	75	75	M6x40
3/4"	260	175	175	M8x45
1"	480	350	350	M8x45

Allen T-wrench: simple and easy

Pressurizing is carried out with the supplied allen T-wrench. By simply turning an allen T-wrench a few turns to the end position max 6 Nm, the system is fully pressurized and the HYDRO-GRIP is centered and fastened in just a few seconds. The G2 chuck is balanced to G 2,5 at 25000 rpm. The runout is measured at 3xD and the max runout is 0,006 mm. A normally balanced chuck and tool unit can be used up to a maximum speed of 25000 rpm.

Assembly Instructions



- ① The tool and G2 chuck must be thoroughly cleaned, removing all traces of grease and other impurities.



- ② Place the tool in the chuck.



- ③ Tighten the pressurizing screw until it stops, max 6 Nm! Any higher tightening torque will not increase the fastening force.



- ④ The tool shank (not for solid carbide tools) must be equipped with a min thread depth of 18 mm. Thread size according to specification.



- ⑤ The G2 chuck and tool unit is now ready to be installed on the woodworking machine.