SILVYN® AFG-PA

SILVYN® AFG-PA is a one-piece connection flange especially designed for SILVYN® MAXI PA



Reliability

Robust

Assembly time

Benefits
Tear-resistant connection
Secure conduit insertion

Application range
In combination with protective conduit
SILVYN® MAXI PA
Mechanical engineering
Bundling and guiding of cables and wires

Norm references / Approvals
UL FILENUMBER E308201

Product Make-up
One-piece connector with clap mechanism specifically designed for use with the SILVYN® MAXI PA. Thanks to the special design, the conduit can be pre-locked and mounted ready for connection

Last Update (10.08.2017)
©2017 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

SILVYN® AFG-PA

Technical Data

Classification:	ETIM 5.0 Class-ID: EC001176 ETIM 5.0 Class-Description: Screw connection for corrugated plastic hose
Colour delivered:	Grey (RAL 7001) Black (RAL 9005), UV-resistant
Material:	PA6 Halogen-free
Protection rating:	IP 54 IP 65 with AFG-PA/AFW-PA seal
Temperature range:	-40 °C to +115 °C

Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

©2017 Lapp Group - Technical changes reserved

SILVYN® AFG-PA

Article number	Nominal size
SILVYN® AFG-PA grey	
55001080	70
55001081	95
SILVYN® AFG-PA black	
55001085	70
55001086	95

Last Update (10.08.2017)
©2017 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16