





Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage Δ [V]	Base voltage Y [V]	Protection	Ins. Cl.		
4.0	S6-60%	2800	50	230	400	IP54	F		
Min speed [rpm]		Max speed [rpm]	Max freq. [Hz]	Absorb. Δ [A]	Absorb. Y [A]	Part number on nameplate			
2800		3000	50	15.2	8.8	COM71800361			
Balancing: G2.5 - ISO 1940 @ maximum motor speed		Balancing type		tool type full key 	tool type half key 	Peso / weight			
						24.59 kg			
Tolleranze non quotate / unlisted tollerances: ±0.5mm Smussi non quotati / unlisted chamfers: ±0.5mm				$\nabla = 0.8 \nabla$	$\nabla = 3.2 \nabla$	$\nabla = 12.5 \nabla$	$\sim = \nabla$	Title	
								7180-C-SB-BT-BR-LH	
rev. n°	description			date	signature	Customer			
00	Emissione			06/04/2017	D. Bottarel	Catalogo			
drawing code						Drawing n°			
COM71800361						5219			
drawn - date	approved - date	checked - date	sostituisce il		foglio / sheet	scala			
E. Gaspari - 06/04/2017	S. Perli - 06/04/2017	S. Perli - 06/04/2017	sostituito dal		1 / 1	n.d.	A4		