



Vite TCEI UNI 5931
M8 x 20 cl. res. 8.8
brunita

Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage Δ [V]	Base voltage Y [V]	Protection	Ins. Cl.
1.7	S1	2800	50	230	400	IP54	F
Min speed [rpm]		Max speed [rpm]	Max freq. [Hz]	Absorb. Δ [A]	Absorb. Y [A]	Part number on nameplate	
2800		4500	75			COM60670060	
Balancing: G2.5 - ISO 1940 @ maximum motor speed		Balancing type		tool type full key	tool type half key	Peso / weight	
						19.25 kg	
Tolleranze non quotate / unlisted tollerances: ±0.5mm Smussi non quotati / unlisted chamfers: ±0.5mm				$\nabla = 0.8 \nabla$	$\nabla = 3.2 \nabla$	$\nabla = 12.5 \nabla$	$\sim = \nabla$
rev. n°	description			date	signature	Customer	
00	Emissione			13/07/2017	D. Bottarel	Catalogo	
drawing - date						approved - date	checked - date
E. Gaspari - 13/07/2017						S. Perli - 13/07/2017	S. Perli - 13/07/2017
sostituisce il				sostituito dal		foglio / sheet	scala
						1 / 1	n.d.



Teknomotor S.r.l.
Via Argenege 31, I-32038 Quero Vas (BL)
www.teknomotor.com

Title
6067-D-SB-BT

Customer
Catalogo

Drawing code
COM60670060

Drawing n°
5382

