

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Protective conductor terminal block, number of connections: 4, connection method: Push-in connection, cross section: 0.5 mm² - 10 mm², mounting type: NS 35/7,5, NS 35/15, color: green-yellow



Your advantages

- Time-saving conductor connection thanks to tool-free direct-connection technology
- Vibration-resistant and maintenance-free conductor connection
- Full flexibility thanks to the standardized CLIPLINE complete bridging, marking, and testing accessories
- Meet the requirements of DIN EN 60947-7-2 or IEC 60947-7-2 for protective conductor connections
- High level of safety thanks to the low-resistance connection to the ground potential via the top-hat rail
- Direct contacting with the DIN rail enables fast, error-free grounding without additional wiring effort.

Commercial data

Item number	3212950
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	BE2223
Product key	BE2223
GTIN	4046356538145
Weight per piece (including packing)	29,221 g
Weight per piece (excluding packing)	29,221 g
Customs tariff number	85369010
Country of origin	CN

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

Technical data

Notes

General

Note	The max. load current must not be exceeded by the total current of all connected conductors.
------	--

Product properties

Product family	PT
Area of application	Railway industry
	Machine building
	Plant engineering
Number of connections	4
Number of rows	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	1.31 W

Connection data

Number of connections per level	4
Nominal cross section	6 mm ²
Connection method	Push-in connection
Note	Please observe the current carrying capacity of the DIN rails.
Stripping length	10 mm ... 12 mm
Internal cylindrical gage	A5
Connection in acc. with standard	IEC 60947-7-2
Conductor cross-section rigid	0.5 mm ² ... 10 mm ²
Cross section AWG	20 ... 8 (converted acc. to IEC)
Conductor cross-section flexible	0.5 mm ² ... 10 mm ²
Conductor cross-section, flexible [AWG]	20 ... 8 (converted acc. to IEC)
Conductor cross-section flexible ultrasound-compressed	0.34 mm ² ... 10 mm ²
Conductor cross-section, flexible [AWG] ultrasound-compressed	22 ... 8 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.5 mm ² ... 6 mm ²
Flexible conductor cross-section (ferrule with plastic sleeve)	0.5 mm ² ... 6 mm ²

Connection cross sections directly pluggable

Conductor cross-section rigid	1 mm ² ... 10 mm ²
Conductor cross-section flexible (ferrule without plastic sleeve)	1 mm ² ... 6 mm ²
Flexible conductor cross-section (ferrule with plastic sleeve)	1 mm ² ... 6 mm ²

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

Ex data

Rated data (ATEX/IECEx)

Identification	Ⓜ II 2 GD Ex eb IIC Gb
Operating temperature range (1)	-60 °C ... 85 °C
Operating temperature range (2)	-40 °C ... 110 °C
Ex-certified accessories	3212963 D-PT 6-QUATTRO 1204520 SZF 2-0,8X4,0 3022276 CLIPFIX 35-5 3022218 CLIPFIX 35
output	(Permanent)

Ex connection data General

Nominal cross section	6 mm ²
Rated cross section AWG	10
Connection capacity rigid	0.5 mm ² ... 10 mm ²
Connection capacity AWG	20 ... 8
Connection capacity flexible	0.5 mm ² ... 6 mm ²
Connection capacity AWG	20 ... 10

Dimensions

Width	8.2 mm
End cover width	2.2 mm
Height	90.5 mm
Depth	42.2 mm
Depth on NS 35/7,5	43.5 mm
Depth on NS 35/15	51 mm

Material specifications

Color	green-yellow
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Environmental and real-life conditions

Oscillation/broadband noise

Specification	DIN EN 50155 (VDE 0115-200):2008-03
Spectrum	Long life test category 2, bogie-mounted
Frequency	$f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$
ASD level	$6.12 \text{ (m/s}^2\text{)}/\text{Hz}$
Acceleration	3.12g
Test duration per axis	5 h
Test directions	X-, Y- and Z-axis
Result	Test passed

Shocks

Specification	DIN EN 50155 (VDE 0115-200):2008-03
Pulse shape	Half-sine
Acceleration	30g
Shock duration	18 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-2
----------------------------------	---------------

Mounting

Mounting type	NS 35/7,5
	NS 35/15

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

Drawings

Circuit diagram



PT 6-QUATTRO-PE - Protective conductor terminal block





3212950

<https://www.phoenixcontact.com/nl/products/3212950>


Approvals


To download certificates, visit the product detail page: <https://www.phoenixcontact.com/nl/products/3212950>


 CSA Approval ID: 2030668				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
B	-	-	20 - 8	-
C	-	-	20 - 8	-
D	-	-	20 - 8	-

 IECEE CB Scheme Approval ID: DE1-65860				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
keine	-	-	-	0.5 - 6

 EAC Approval ID: RU C-DE.BL08.B.00644				
---	--	--	--	--

 cULus Recognized Approval ID: E60425				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
B	-	-	20 - 8	-
C	-	-	20 - 8	-
F	-	-	20 - 8	-
D	-	-	20 - 8	-

 LR Approval ID: LR2371832TA				
---	--	--	--	--


 ClassNK Approval ID: 22ME0007				
---	--	--	--	--


PT 6-QUATTRO-PE - Protective conductor terminal block



3212950


<https://www.phoenixcontact.com/nl/products/3212950>

 VDE Zeichengenehmigung Approval ID: 40035188				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
keine				
	-	-	-	0.5 - 6

 PRS Approval ID: TE/2107/880590/21				
--	--	--	--	--


ABS Approval ID: 21-2192245-PDA				
---	--	--	--	--

DNV Approval ID: TAE000010T				
---------------------------------------	--	--	--	--


 cUL Recognized Approval ID: E192998				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
keine				
	-	-	20 - 8	-

 EAC Ex Approval ID: RU C-DE.AB72.B.02351				
--	--	--	--	--

 IECEx Approval ID: IECEx SEV13.0005U				
--	--	--	--	--

 UL Recognized Approval ID: E192998				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
keine				
	-	-	20 - 8	-

 ATEX Approval ID: SEV13ATEX0159U				
--	--	--	--	--

 CCC				
--	--	--	--	--

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

Approval ID: 2020322313000631



EAC Ex

Approval ID: KZ 7500525010101950

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

Classifications

ECLASS

ECLASS-13.0	27250103
ECLASS-15.0	27250103

ETIM

ETIM 9.0	EC000901
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

Accessories

FBS 2-8 - Plug-in bridge

3030284

<https://www.phoenixcontact.com/nl/products/3030284>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, nominal current: 41 A, color: red

FBS 3-8 - Plug-in bridge

3030297

<https://www.phoenixcontact.com/nl/products/3030297>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, nominal current: 41 A, color: red

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

FBS 4-8 - Plug-in bridge

3030307

<https://www.phoenixcontact.com/nl/products/3030307>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, nominal current: 41 A, color: red

FBS 5-8 - Plug-in bridge

3030310

<https://www.phoenixcontact.com/nl/products/3030310>



Plug-in bridge, pitch: 8.2 mm, number of positions: 5, nominal current: 41 A, color: red

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

FBS 6-8 - Plug-in bridge

3032470

<https://www.phoenixcontact.com/nl/products/3032470>



Plug-in bridge, pitch: 8.2 mm, number of positions: 6, nominal current: 41 A, color: red

FBS 10-8 - Plug-in bridge

3030323

<https://www.phoenixcontact.com/nl/products/3030323>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, nominal current: 41 A, color: red

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

FBS 2-8 CT - Plug-in bridge

3033830

<https://www.phoenixcontact.com/nl/products/3033830>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, nominal current: 41 A, color: orange

FBS 3-8 CT - Plug-in bridge

3033831

<https://www.phoenixcontact.com/nl/products/3033831>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, nominal current: 41 A, color: orange

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

FBS 4-8 CT - Plug-in bridge

3033832

<https://www.phoenixcontact.com/nl/products/3033832>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, nominal current: 41 A, color: orange

FBS 10-8 CT - Plug-in bridge

3033833

<https://www.phoenixcontact.com/nl/products/3033833>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, nominal current: 41 A, color: orange

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

FBS 2-8 BU - Plug-in bridge

3032567

<https://www.phoenixcontact.com/nl/products/3032567>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, nominal current: 41 A, color: blue

FBS 3-8 BU - Plug-in bridge

3032570

<https://www.phoenixcontact.com/nl/products/3032570>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, nominal current: 41 A, color: blue

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

FBS 4-8 BU - Plug-in bridge

3032583

<https://www.phoenixcontact.com/nl/products/3032583>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, nominal current: 41 A, color: blue

FBS 5-8 BU - Plug-in bridge

3032596

<https://www.phoenixcontact.com/nl/products/3032596>



Plug-in bridge, pitch: 8.2 mm, number of positions: 5, nominal current: 41 A, color: blue

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

FBS 6-8 BU - Plug-in bridge

3032677

<https://www.phoenixcontact.com/nl/products/3032677>



Plug-in bridge, pitch: 8.2 mm, number of positions: 6, nominal current: 41 A, color: blue

FBS 10-8 BU - Plug-in bridge

3032606

<https://www.phoenixcontact.com/nl/products/3032606>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, nominal current: 41 A, color: blue

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

FBS 2-8 GY - Plug-in bridge

3032621

<https://www.phoenixcontact.com/nl/products/3032621>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, nominal current: 41 A, color: gray

FBS 3-8 GY - Plug-in bridge

3032622

<https://www.phoenixcontact.com/nl/products/3032622>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, nominal current: 41 A, color: gray

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

FBS 4-8 GY - Plug-in bridge

3032635

<https://www.phoenixcontact.com/nl/products/3032635>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, nominal current: 41 A, color: gray

FBS 5-8 GY - Plug-in bridge

3032648

<https://www.phoenixcontact.com/nl/products/3032648>



Plug-in bridge, pitch: 8.2 mm, number of positions: 5, nominal current: 41 A, color: gray

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

FBS 6-8 GY - Plug-in bridge

3032664

<https://www.phoenixcontact.com/nl/products/3032664>



Plug-in bridge, pitch: 8.2 mm, number of positions: 6, nominal current: 41 A, color: gray

FBS 10-8 GY - Plug-in bridge

3032651

<https://www.phoenixcontact.com/nl/products/3032651>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, nominal current: 41 A, color: gray

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

FBSRH 2-8 - Short-circuit connector

3033802

<https://www.phoenixcontact.com/nl/products/3033802>



Short-circuit connector, pitch: 8.2 mm, number of positions: 2, nominal current: 32 A, color: red

FBSRH 3-8 - Short-circuit connector

3033803

<https://www.phoenixcontact.com/nl/products/3033803>



Short-circuit connector, pitch: 8.2 mm, number of positions: 3, nominal current: 32 A, color: red

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

FBSRH 4-8 - Short-circuit connector

3033804

<https://www.phoenixcontact.com/nl/products/3033804>



Short-circuit connector, pitch: 8.2 mm, number of positions: 4, nominal current: 32 A, color: red

FBSR 2-8 - Plug-in bridge

3033808

<https://www.phoenixcontact.com/nl/products/3033808>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, nominal current: 32 A, color: red

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

FBSR 3-8 - Plug-in bridge

3001597

<https://www.phoenixcontact.com/nl/products/3001597>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, nominal current: 32 A, color: red

FBSR 4-8 - Plug-in bridge

3000585

<https://www.phoenixcontact.com/nl/products/3000585>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, nominal current: 32 A, color: red

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

FBSR 5-8 - Plug-in bridge

3033809

<https://www.phoenixcontact.com/nl/products/3033809>



Plug-in bridge, pitch: 8.2 mm, number of positions: 5, nominal current: 32 A, color: red

FBSR 10-8 - Plug-in bridge

3001599

<https://www.phoenixcontact.com/nl/products/3001599>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, nominal current: 32 A, color: red

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

FBSR 16-8 - Plug-in bridge

3033816

<https://www.phoenixcontact.com/nl/products/3033816>



Plug-in bridge, pitch: 8.2 mm, number of positions: 16, nominal current: 32 A, color: red

D-PT 6-QUATTRO - End cover

3212963

<https://www.phoenixcontact.com/nl/products/3212963>



End cover, depth: 36 mm, width: 2.2 mm, height: 90.5 mm, color: gray

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

WS PT 6 - Warning label

1029029

<https://www.phoenixcontact.com/nl/products/1029029>



Warning label, yellow/black, labeled: Lightning flash, mounting type: plug in, for terminal block width: 8.2 mm

NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/nl/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/nl/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: silver-colored

NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/nl/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/nl/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/nl/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: silver-colored

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/nl/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver-colored

NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/nl/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/nl/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/nl/products/1201798>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver-colored

PT 6-QUATTRO-PE - Protective conductor terminal block


3212950

<https://www.phoenixcontact.com/nl/products/3212950>

ZB 8:UNBEDRUCKT - Zack marker strip

1052002

<https://www.phoenixcontact.com/nl/products/1052002>




Zack marker strip, Strip, white, unmarked, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 10, text field height: 10.5 mm, text field width: 8.15 mm

ZB 8 CUS - Zack marker strip

0825011

<https://www.phoenixcontact.com/nl/products/0825011>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, Number of individual labels: 10, text field height: 8.15 mm, text field width: 10.5 mm

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

UC-TM 8 - Marker for terminal blocks

0818072

<https://www.phoenixcontact.com/nl/products/0818072>



Marker for terminal blocks, Sheet, white, unmarked, can be labeled with: BLUEMARK E.CARD, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 56, text field height: 10.5 mm, text field width: 7.6 mm

UC-TM 8 CUS - Marker for terminal blocks

0824597

<https://www.phoenixcontact.com/nl/products/0824597>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, Number of individual labels: 56, text field height: 10.5 mm, text field width: 7.6 mm

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

UCT-TM 8 - Marker for terminal blocks

0828740

<https://www.phoenixcontact.com/nl/products/0828740>



Marker for terminal blocks, Sheet, white, unmarked, can be labeled with: BLUEMARK E.CARD, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME 2.0, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, TOPMARK NEO, TOPMARK LASER, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 42, text field height: 10.5 mm, text field width: 7.6 mm

UCT-TM 8 CUS - Marker for terminal blocks

0829616

<https://www.phoenixcontact.com/nl/products/0829616>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, Number of individual labels: 42, text field height: 10.5 mm, text field width: 7.6 mm

PT 6-QUATTRO-PE - Protective conductor terminal block


3212950

<https://www.phoenixcontact.com/nl/products/3212950>

ZB 8,LGS:L1-N,PE - Marker for terminal blocks

1052413

<https://www.phoenixcontact.com/nl/products/1052413>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 10, text field height: 10.5 mm, text field width: 8.15 mm

ZBF 8:UNBEDRUCKT - Zack Marker strip, flat

0808781

<https://www.phoenixcontact.com/nl/products/0808781>



Zack Marker strip, flat, Strip, white, unmarked, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 8 mm, Number of individual labels: 10, text field height: 8.15 mm, text field width: 5.15 mm

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

ZBF 8 CUS - Zack Marker strip, flat

0825030

<https://www.phoenixcontact.com/nl/products/0825030>



Zack Marker strip, flat, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8 mm, Number of individual labels: 10, text field height: 8.15 mm, text field width: 5.15 mm

UC-TMF 8 - Marker for terminal blocks

0818137

<https://www.phoenixcontact.com/nl/products/0818137>



Marker for terminal blocks, Sheet, white, unmarked, can be labeled with: BLUEMARK E.CARD, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 56, text field height: 5.1 mm, text field width: 7.6 mm

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

UC-TMF 8 CUS - Marker for terminal blocks

0824654

<https://www.phoenixcontact.com/nl/products/0824654>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8.2 mm, Number of individual labels: 56, text field height: 5.1 mm, text field width: 7.6 mm

UCT-TMF 8 - Marker for terminal blocks

0828748

<https://www.phoenixcontact.com/nl/products/0828748>



Marker for terminal blocks, Sheet, white, unmarked, can be labeled with: BLUEMARK E.CARD, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME 2.0, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, TOPMARK NEO, TOPMARK LASER, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 42, text field height: 4.7 mm, text field width: 7.4 mm

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

UCT-TMF 8 CUS - Marker for terminal blocks

0829672

<https://www.phoenixcontact.com/nl/products/0829672>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8.2 mm, Number of individual labels: 42, text field height: 4.7 mm, text field width: 7.4 mm

MPS-MT - Test plug

0201744

<https://www.phoenixcontact.com/nl/products/0201744>



Test plug, with solder connection up to 1 mm² conductor cross-section, number of positions: 1, color: gray

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

MPS-IH WH - Insulating sleeve

0201663

<https://www.phoenixcontact.com/nl/products/0201663>

Insulating sleeve, color: white



MPS-IH RD - Insulating sleeve

0201676

<https://www.phoenixcontact.com/nl/products/0201676>

Insulating sleeve, color: red



PT 6-QUATTRO-PE - Protective conductor terminal block

3212950


<https://www.phoenixcontact.com/nl/products/3212950>

MPS-IH BU - Insulating sleeve

0201689

<https://www.phoenixcontact.com/nl/products/0201689>

Insulating sleeve, color: blue



MPS-IH YE - Insulating sleeve

0201692

<https://www.phoenixcontact.com/nl/products/0201692>

Insulating sleeve, color: yellow



PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

MPS-IH GN - Insulating sleeve

0201702

<https://www.phoenixcontact.com/nl/products/0201702>

Insulating sleeve, color: green



MPS-IH GY - Insulating sleeve

0201728

<https://www.phoenixcontact.com/nl/products/0201728>

Insulating sleeve, color: gray



PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

MPS-IH BK - Insulating sleeve

0201731

<https://www.phoenixcontact.com/nl/products/0201731>

Insulating sleeve, color: black



PAI-4-FIX BU - Test adapter

3032729

<https://www.phoenixcontact.com/nl/products/3032729>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: blue

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

PAI-4-FIX OG - Test adapter

3034455

<https://www.phoenixcontact.com/nl/products/3034455>



4 mm test adapter, for terminal blocks with 8.2 mm pitch

PAI-4-FIX YE - Test adapter

3032745

<https://www.phoenixcontact.com/nl/products/3032745>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: yellow

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

PAI-4-FIX RD - Test adapter

3032732

<https://www.phoenixcontact.com/nl/products/3032732>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: red

PAI-4-FIX GN - Test adapter

3032758

<https://www.phoenixcontact.com/nl/products/3032758>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: green

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

PAI-4-FIX BK - Test adapter

3032774

<https://www.phoenixcontact.com/nl/products/3032774>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: black

PAI-4-FIX GY - Test adapter

3032790

<https://www.phoenixcontact.com/nl/products/3032790>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: gray

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

PAI-4-FIX VT - Test adapter

3032761

<https://www.phoenixcontact.com/nl/products/3032761>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: violet

PAI-4-FIX BN - Test adapter

3032787

<https://www.phoenixcontact.com/nl/products/3032787>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: brown

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

PAI-4-FIX WH - Test adapter

3032797

<https://www.phoenixcontact.com/nl/products/3032797>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: white

PAIS-4-FIX GY - Test adapter

3032791

<https://www.phoenixcontact.com/nl/products/3032791>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: gray

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

PAIS-4-FIX BK - Test adapter

3032792

<https://www.phoenixcontact.com/nl/products/3032792>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: black

PAIS-4-FIX RD - Test adapter

3032793

<https://www.phoenixcontact.com/nl/products/3032793>



Test adapter, Do not plug in while the power is connected, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: red

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

PAIS-4-FIX BU - Test adapter

3032798

<https://www.phoenixcontact.com/nl/products/3032798>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: blue

PAIS-4-FIX YE - Test adapter

3032799

<https://www.phoenixcontact.com/nl/products/3032799>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: yellow

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

PAIS-4-FIX GN - Test adapter

3032801

<https://www.phoenixcontact.com/nl/products/3032801>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: green

PAIS-4-FIX VT - Test adapter

3032802

<https://www.phoenixcontact.com/nl/products/3032802>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: violet

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

PS-8 - Test plug

3031005

<https://www.phoenixcontact.com/nl/products/3031005>



Test plug, Modular test plug, number of positions: 1, color: red

DP PS-8 - Spacer plate

3036741

<https://www.phoenixcontact.com/nl/products/3036741>



Spacer plate, depth: 29 mm, width: 8.2 mm, height: 22.4 mm, number of positions: 1, color: red

PT 6-QUATTRO-PE - Protective conductor terminal block

3212950

<https://www.phoenixcontact.com/nl/products/3212950>

PS-8/2,3MM RD - Test plug

3048564

<https://www.phoenixcontact.com/nl/products/3048564>



Test plug, number of positions: 1, color: red

TMT (EX9,5)R - Marker for terminal blocks

0828295

<https://www.phoenixcontact.com/nl/products/0828295>



Marker for terminal blocks, Roll, white, unmarked, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: latching, snap into tall marker groove, for terminal block width: 30000 mm, Number of individual labels: 1, roll length: 30 m, text field height: 9.5 mm, text field width: 50000 mm

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

US-TM 100 - Marker for terminal blocks

0829255

<https://www.phoenixcontact.com/nl/products/0829255>



Marker for terminal blocks, Card, white, unmarked, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, THERMOMARK PRIME 2.0, mounting type: latching, Number of individual labels: 13, text field height: 9.8 mm, text field width: 104 mm

SZF 2-0,8X4,0 - Screwdriver

1204520

<https://www.phoenixcontact.com/nl/products/1204520>



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.8 x 4.0 x 100 mm, 2-component grip, with non-slip grip

PT 6-QUATTRO-PE - Protective conductor terminal block



3212950

<https://www.phoenixcontact.com/nl/products/3212950>

PROJECT COMPLETE - Software

1050453

<https://www.phoenixcontact.com/nl/products/1050453>



Intuitive planning and marking software for configuring terminal strips and for professional marking of marking materials for terminal blocks, conductors, cables, devices, and systems. The software is available for download

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT B.V.
Hengelder 56 6902 PA Zevenaar
Postbus 246 6900 AE Zevenaar
(0316) 59 17 20
sales@phoenixcontact.nl