

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 1000 V, nominal current: 41 A, number of connections: 4, connection method: Push-in connection, Rated cross section: 6 mm<sup>2</sup>, cross section: 0.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: gray

## Your advantages

- Time-saving conductor connection thanks to tool-free direct-connection technology
- Convenient plugging with lower insertion force
- High conductor pull-out forces due to the spring design
- Vibration-resistant and maintenance-free conductor connection
- Full flexibility thanks to the standardized CLIPLINE complete bridging, marking, and testing accessories
- Compact wiring of three conductors in a single terminal block
- Optimized for manual and automated wiring

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 3212934       |
| Packing unit                         | 50 pc         |
| Minimum order quantity               | 50 pc         |
| Sales key                            | BE2213        |
| Product key                          | BE2213        |
| GTIN                                 | 4046356538121 |
| Weight per piece (including packing) | 25,3 g        |
| Weight per piece (excluding packing) | 25,3 g        |
| Customs tariff number                | 85369010      |
| Country of origin                    | CN            |

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## Technical data

### Product properties

|                       |                   |
|-----------------------|-------------------|
| Product family        | PT                |
| Area of application   | Railway industry  |
|                       | Machine building  |
|                       | Plant engineering |
| Number of connections | 4                 |
| Number of rows        | 1                 |
| Potentials            | 1                 |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|   |        |
|---|--------|
| Rated surge voltage                             | 8 kV   |
| Maximum power dissipation for nominal condition | 1.31 W |

### Connection data

|   |   |
|---|---|
| Number of connections per level   | 4   |
| Nominal cross section   | 6 mm <sup>2</sup>   |
| Connection method   | Push-in connection  |
| Stripping length  | 10 mm ... 12 mm   |
| Internal cylindrical gage   | A5  |
| Connection in acc. with standard  | IEC 60947-7-1   |
| Conductor cross-section rigid   | 0.5 mm <sup>2</sup> ... 10 mm <sup>2</sup>  |
| Cross section AWG   | 20 ... 8 (converted acc. to IEC)  |
| Conductor cross-section flexible  | 0.5 mm <sup>2</sup> ... 10 mm <sup>2</sup>  |
| Conductor cross-section, flexible [AWG]   | 20 ... 8 (converted acc. to IEC)  |
| Conductor cross-section flexible ultrasound-compressed                                    | 0.34 mm <sup>2</sup> ... 10 mm <sup>2</sup>   |
| Conductor cross-section, flexible [AWG] ultrasound-compressed                             | 22 ... 8 (converted acc. to IEC)  |
| Conductor cross-section flexible (ferrule without plastic sleeve)                         | 0.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>   |
| Flexible conductor cross-section (ferrule with plastic sleeve)                            | 0.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>   |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> When using TWIN ferrules, we recommend a minimum ferrule length of 13 mm. |
| Nominal current   | 41 A  |
| Maximum load current  | 52 A (with 10 mm <sup>2</sup> conductor cross-section, rigid)   |
| Nominal voltage   | 1000 V  |
| Nominal cross section   | 6 mm <sup>2</sup>   |

### Connection cross sections directly pluggable

|   |  |
|---|--|
| Conductor cross-section rigid                                     | 1 mm <sup>2</sup> ... 10 mm <sup>2</sup> |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 1 mm <sup>2</sup> ... 6 mm <sup>2</sup>  |
| Flexible conductor cross-section (ferrule with plastic sleeve)    | 1 mm <sup>2</sup> ... 6 mm <sup>2</sup>  |

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## Ex data

### Rated data (ATEX/IECEX)

|  |   |
|--|---|
| Identification   | Ⓜ II 2 GD Ex eb IIC Gb  |
| Operating temperature range (1)  | -60 °C ... 85 °C  |
| Operating temperature range (2)  | -40 °C ... 110 °C   |
| Ex-certified accessories   | 3212963 D-PT 6-QUATTRO<br>1204520 SZF 2-0,8X4,0<br>3022276 CLIPFIX 35-5<br>3022218 CLIPFIX 35   |
| List of bridges  | Plug-in bridge / FBS 2-8 / 3030284<br>Plug-in bridge / FBS 3-8 / 3030297<br>Plug-in bridge / FBS 4-8 / 3030307<br>Plug-in bridge / FBS 5-8 / 3030310<br>Plug-in bridge / FBS 10-8 / 3030323 |
| Bridge data  | 35 A (6 mm <sup>2</sup> )   |
| Ex temperature increase<br>for bridging with bridge                      | 40 K (36 A/6 mm <sup>2</sup> )<br>550 V   |
| - At bridging between non-adjacent terminal blocks                       | 275 V   |
| - At bridging between non-adjacent terminal blocks via PE terminal block | 275 V   |
| - At cut-to-length bridging  | 220 V   |
| - At cut-to-length bridging with cover                                   | 275 V   |
| Rated insulation voltage   | 500 V   |
| output   | (Permanent)   |

### Ex level General

|                      |         |
|----------------------|---------|
| Rated current        | 36 A    |
| Maximum load current | 45 A    |
| Contact resistance   | 0.65 mΩ |

### Ex connection data General

|                              |  |
|------------------------------|--|
| Nominal cross section        | 6 mm <sup>2</sup>                          |
| Rated cross section AWG      | 10   |
| Connection capacity rigid    | 0.5 mm <sup>2</sup> ... 10 mm <sup>2</sup> |
| Connection capacity AWG      | 20 ... 8                                   |
| Connection capacity flexible | 0.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>  |
| Connection capacity AWG      | 20 ... 10                                  |

## Dimensions

|                    |         |
|--------------------|---------|
| Width              | 8.2 mm  |
| End cover width    | 2.2 mm  |
| Height             | 90.5 mm |
| Depth              | 42.2 mm |
| Depth on NS 35/7,5 | 43.5 mm |

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

|                   |       |
|-------------------|-------|
| Depth on NS 35/15 | 51 mm |
|-------------------|-------|

## Material specifications

|  |                 |
|--|-----------------|
| Color  | gray (RAL 7042) |
| Flammability rating according to UL 94                           | V0              |
| Insulating material group  | I               |
| Insulating material  | PA              |
| Static insulating material application in cold                   | -60 °C          |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C          |
| Fire protection for rail vehicles (DIN EN 45545-2) R22           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R23           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R24           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R26           | HL 1 - HL 3     |
| Surface flammability NFPA 130 (ASTM E 162)                       | passed          |
| Specific optical density of smoke NFPA 130 (ASTM E 662)          | passed          |
| Smoke gas toxicity NFPA 130 (SMP 800C)                           | passed          |

## Electrical tests

### Surge voltage test

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 9.8 kV      |
| Result                | Test passed |

### Temperature-rise test

|  |                                     |
|--|-------------------------------------|
| Requirement temperature-rise test              | Increase in temperature $\leq 45$ K |
| Result   | Test passed                         |
|  | Test passed                         |
| Short-time withstand current 6 mm <sup>2</sup> | 0.72 kA                             |
| Result   | Test passed                         |

### Power-frequency withstand voltage

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 2.2 kV      |
| Result                | Test passed |

## Mechanical properties

### Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

## Mechanical tests

### Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

### Attachment on the carrier

|                         |                     |
|-------------------------|---------------------|
| DIN rail/fixing support | NS 35/7,5 UNGELOCHT |
| Test force setpoint     | 5 N                 |

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

|  |                              |
|--|------------------------------|
| Result                                   | Test passed                  |
| Test for conductor damage and slackening |                              |
| Rotation speed                           | 10 rpm                       |
| Revolutions                              | 135                          |
| Conductor cross-section/weight           | 0.5 mm <sup>2</sup> / 0.3 kg |
|  | 6 mm <sup>2</sup> / 1.4 kg   |
|  | 10 mm <sup>2</sup> / 2 kg    |
| Result                                   | Test passed                  |

## Environmental and real-life conditions

### Aging

|                    |             |
|--------------------|-------------|
| Temperature cycles | 192         |
| Result             | Test passed |

### Needle-flame test

|                  |             |
|------------------|-------------|
| Time of exposure | 30 s        |
| Result           | Test passed |

### Oscillation/broadband noise

|                        |  |
|------------------------|--|
| Specification          | DIN EN 50155 (VDE 0115-200):2018-05            |
| Spectrum               | Long life test category 2, bogie-mounted       |
| Frequency              | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level              | 6.12 (m/s <sup>2</sup> ) <sup>2</sup> /Hz      |
| Acceleration           | 3.12g  |
| Test duration per axis | 5 h  |
| Test directions        | X-, Y- and Z-axis                              |
| Result                 | Test passed                                    |

### Shocks

|                                |                                     |
|--------------------------------|-------------------------------------|
| Specification                  | DIN EN 50155 (VDE 0115-200):2018-05 |
| Pulse shape                    | Half-sine                           |
| Acceleration                   | 30g                                 |
| Shock duration                 | 18 ms                               |
| Number of shocks per direction | 3                                   |
| Test directions                | X-, Y- and Z-axis (pos. and neg.)   |
| Result                         | Test passed                         |

### Ambient conditions

|   |  |
|---|--|
| Ambient temperature (operation)         | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport) | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)  |
| Ambient temperature (assembly)          | -5 °C ... 70 °C  |
| Ambient temperature (actuation)         | -5 °C ... 70 °C  |
| Permissible humidity (operation)        | 20 % ... 90 %  |

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

|  |               |
|--|---------------|
| Permissible humidity (storage/transport) | 30 % ... 70 % |
|--|---------------|

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## Drawings

Circuit diagram



# PT 6-QUATTRO - Feed-through terminal block




3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/nl/products/3212934>

|  <b>CSA</b><br>Approval ID: 2030668 |                       |                       |                   |                      |
|--|-----------------------|-----------------------|-------------------|----------------------|
|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
| B  | 600 V                 | 40 A                  | 20 - 8            | -                    |
| C  | 600 V                 | 40 A                  | 20 - 8            | -                    |
| D  | 600 V                 | 5 A                   | 20 - 8            | -                    |

|  <b>IECEE CB Scheme</b><br>Approval ID: DE1-64280 |  |  |  |  |
|--|--|--|--|--|
|--|--|--|--|--|

|  <b>EAC</b><br>Approval ID: RU C-DE.BL08.B.00644 |  |  |  |  |
|---|--|--|--|--|
|---|--|--|--|--|

|  <b>cULus Recognized</b><br>Approval ID: E60425 |                       |                       |                   |                      |
|--|-----------------------|-----------------------|-------------------|----------------------|
|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
| B  | 600 V                 | 40 A                  | 20 - 8            | -                    |
| C  | 600 V                 | 40 A                  | 20 - 8            | -                    |
| F  | 1000 V                | 40 A                  | 20 - 8            | -                    |

|  <b>LR</b><br>Approval ID: LR2371832TA |  |  |  |  |
|---|--|--|--|--|
|---|--|--|--|--|

|  <b>NK</b><br>Approval ID: 22ME0007 |  |  |  |  |
|--|--|--|--|--|
|--|--|--|--|--|

|  <b>VDE Zeichengenehmigung</b><br>Approval ID: 40035239 |                       |                       |                   |                      |
|--|-----------------------|-----------------------|-------------------|----------------------|
|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
| keine  |                       |                       |                   |                      |

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

|                          |        |      |   |          |
|--------------------------|--------|------|---|----------|
| Only flexible conductors | 1000 V | 41 A | - | 0.5 - 6  |
| Only rigid conductors    | 1000 V | 41 A | - | 0.5 - 10 |



**PRC**

Approval ID: TE/2107/880590/21

**ABS**

Approval ID: 21-2192245-PDA

**DNV**

Approval ID: TAE000010T



**cUL Recognized**

Approval ID: E192998

|       | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
|-------|-----------------------|-----------------------|-------------------|----------------------|
| keine |                       |                       |                   |                      |
|       | 550 V                 | 40 A                  | 20 - 8            | -                    |



**EAC Ex**

Approval ID: RU C-DE.AB72.B.02351



**IEC Ex**

Approval ID: IECEx SEV13.0005U



**UL Recognized**

Approval ID: E192998

|       | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
|-------|-----------------------|-----------------------|-------------------|----------------------|
| keine |                       |                       |                   |                      |
|       | 550 V                 | 40 A                  | 20 - 8            | -                    |



**ATEX**

Approval ID: SEV13ATEX0159U



**CCC**

Approval ID: 2020322313000631

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>



**EAC Ex**

Approval ID: KZ 7500525010101950

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27250101 |
| ECLASS-15.0 | 27250101 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### China RoHS

|  |  |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|  | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## Accessories

 Note: Applying some accessories below might limit this product.


### FBS 2-8 - Plug-in bridge

3030284

<https://www.phoenixcontact.com/nl/products/3030284>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, nominal current: 41 A, color: red

 Max. current carrying capacity: 41 A


### FBS 3-8 - Plug-in bridge

3030297

<https://www.phoenixcontact.com/nl/products/3030297>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, nominal current: 41 A, color: red

 Max. current carrying capacity: 41 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>


## FBS 4-8 - Plug-in bridge

3030307

<https://www.phoenixcontact.com/nl/products/3030307>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, nominal current: 41 A, color: red

 Max. current carrying capacity: 41 A

---


## FBS 5-8 - Plug-in bridge

3030310

<https://www.phoenixcontact.com/nl/products/3030310>



Plug-in bridge, pitch: 8.2 mm, number of positions: 5, nominal current: 41 A, color: red

 Max. current carrying capacity: 41 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>




## FBS 6-8 - Plug-in bridge

3032470

<https://www.phoenixcontact.com/nl/products/3032470>



Plug-in bridge, pitch: 8.2 mm, number of positions: 6, nominal current: 41 A, color: red

 Max. current carrying capacity: 41 A

---


## FBS 10-8 - Plug-in bridge

3030323

<https://www.phoenixcontact.com/nl/products/3030323>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, nominal current: 41 A, color: red

 Max. current carrying capacity: 41 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## FBS 2-8 CT - Plug-in bridge

3033830

<https://www.phoenixcontact.com/nl/products/3033830>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, nominal current: 41 A, color: orange

 Max. current carrying capacity: 41 A

---


## FBS 3-8 CT - Plug-in bridge

3033831

<https://www.phoenixcontact.com/nl/products/3033831>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, nominal current: 41 A, color: orange

 Max. current carrying capacity: 41 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>




## FBS 4-8 CT - Plug-in bridge

3033832

<https://www.phoenixcontact.com/nl/products/3033832>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, nominal current: 41 A, color: orange

 Max. current carrying capacity: 41 A

---


## FBS 10-8 CT - Plug-in bridge

3033833

<https://www.phoenixcontact.com/nl/products/3033833>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, nominal current: 41 A, color: orange

 Max. current carrying capacity: 41 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## FBS 2-8 BU - Plug-in bridge

3032567

<https://www.phoenixcontact.com/nl/products/3032567>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, nominal current: 41 A, color: blue

 Max. current carrying capacity: 41 A

---


## FBS 3-8 BU - Plug-in bridge

3032570

<https://www.phoenixcontact.com/nl/products/3032570>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, nominal current: 41 A, color: blue

 Max. current carrying capacity: 41 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>


## FBS 4-8 BU - Plug-in bridge

3032583

<https://www.phoenixcontact.com/nl/products/3032583>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, nominal current: 41 A, color: blue

 Max. current carrying capacity: 41 A

---


## FBS 5-8 BU - Plug-in bridge

3032596

<https://www.phoenixcontact.com/nl/products/3032596>



Plug-in bridge, pitch: 8.2 mm, number of positions: 5, nominal current: 41 A, color: blue

 Max. current carrying capacity: 41 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## FBS 6-8 BU - Plug-in bridge

3032677

<https://www.phoenixcontact.com/nl/products/3032677>



Plug-in bridge, pitch: 8.2 mm, number of positions: 6, nominal current: 41 A, color: blue

 Max. current carrying capacity: 41 A

---


## FBS 10-8 BU - Plug-in bridge

3032606

<https://www.phoenixcontact.com/nl/products/3032606>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, nominal current: 41 A, color: blue

 Max. current carrying capacity: 41 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## FBS 2-8 GY - Plug-in bridge

3032621

<https://www.phoenixcontact.com/nl/products/3032621>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, nominal current: 41 A, color: gray

 Max. current carrying capacity: 41 A

---

## FBS 3-8 GY - Plug-in bridge

3032622

<https://www.phoenixcontact.com/nl/products/3032622>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, nominal current: 41 A, color: gray

 Max. current carrying capacity: 41 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## FBS 4-8 GY - Plug-in bridge

3032635

<https://www.phoenixcontact.com/nl/products/3032635>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, nominal current: 41 A, color: gray

 Max. current carrying capacity: 41 A

---


## FBS 5-8 GY - Plug-in bridge

3032648

<https://www.phoenixcontact.com/nl/products/3032648>



Plug-in bridge, pitch: 8.2 mm, number of positions: 5, nominal current: 41 A, color: gray

 Max. current carrying capacity: 41 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## FBS 6-8 GY - Plug-in bridge

3032664

<https://www.phoenixcontact.com/nl/products/3032664>



Plug-in bridge, pitch: 8.2 mm, number of positions: 6, nominal current: 41 A, color: gray

 Max. current carrying capacity: 41 A

---

## FBS 10-8 GY - Plug-in bridge

3032651

<https://www.phoenixcontact.com/nl/products/3032651>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, nominal current: 41 A, color: gray

 Max. current carrying capacity: 41 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## FBSRH 2-8 - Short-circuit connector

3033802

<https://www.phoenixcontact.com/nl/products/3033802>



Short-circuit connector, pitch: 8.2 mm, number of positions: 2, nominal current: 32 A, color: red

 Max. current carrying capacity: 32 A

---

## FBSRH 3-8 - Short-circuit connector

3033803

<https://www.phoenixcontact.com/nl/products/3033803>



Short-circuit connector, pitch: 8.2 mm, number of positions: 3, nominal current: 32 A, color: red

 Max. current carrying capacity: 32 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## FBSRH 4-8 - Short-circuit connector

3033804

<https://www.phoenixcontact.com/nl/products/3033804>



Short-circuit connector, pitch: 8.2 mm, number of positions: 4, nominal current: 32 A, color: red

 Max. current carrying capacity: 32 A

---

## FBSR 2-8 - Plug-in bridge

3033808

<https://www.phoenixcontact.com/nl/products/3033808>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, nominal current: 32 A, color: red

 Max. current carrying capacity: 32 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## FBSR 3-8 - Plug-in bridge

3001597

<https://www.phoenixcontact.com/nl/products/3001597>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, nominal current: 32 A, color: red

 Max. current carrying capacity: 32 A

---


## FBSR 4-8 - Plug-in bridge

3000585

<https://www.phoenixcontact.com/nl/products/3000585>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, nominal current: 32 A, color: red

 Max. current carrying capacity: 32 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## FBSR 5-8 - Plug-in bridge

3033809

<https://www.phoenixcontact.com/nl/products/3033809>



Plug-in bridge, pitch: 8.2 mm, number of positions: 5, nominal current: 32 A, color: red

 Max. current carrying capacity: 32 A

---


## FBSR 10-8 - Plug-in bridge

3001599

<https://www.phoenixcontact.com/nl/products/3001599>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, nominal current: 32 A, color: red

 Max. current carrying capacity: 32 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>



## FBSR 16-8 - Plug-in bridge

3033816

<https://www.phoenixcontact.com/nl/products/3033816>



Plug-in bridge, pitch: 8.2 mm, number of positions: 16, nominal current: 32 A, color: red

 Max. current carrying capacity: 32 A

---


## SB-MER 2-8 - Bridge bar

3000587

<https://www.phoenixcontact.com/nl/products/3000587>



Bridge bar, pitch: 8.2 mm, number of positions: 2, nominal current: 25 A, length: 25 mm, color: gray/orange

 Max. current carrying capacity: 24 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## SB-MER 3-8 - Bridge bar

3000588

<https://www.phoenixcontact.com/nl/products/3000588>



Bridge bar, pitch: 8.2 mm, number of positions: 3, nominal current: 25 A, length: 25 mm, color: gray/orange

 Max. current carrying capacity: 24 A

---

## SB-MER 4-8 - Bridge bar

3000589

<https://www.phoenixcontact.com/nl/products/3000589>



Bridge bar, pitch: 8.2 mm, number of positions: 4, nominal current: 25 A, length: 25 mm, color: gray/orange

 Max. current carrying capacity: 24 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## RB ST 6-(2,5/4) - Reducing bridge

3030860

<https://www.phoenixcontact.com/nl/products/3030860>



Reducing bridge, pitch: 9 mm, number of positions: 2, nominal current: 32 A, length: 30 mm, color: red

 Max. current carrying capacity: 35 A

---


## RB 16-6 - Reducing bridge

3047072

<https://www.phoenixcontact.com/nl/products/3047072>



Reducing bridge, pitch: 12.2 mm, number of positions: 2, nominal current: 37 A, color: red

 Max. current carrying capacity: 37 A

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>




## RB ST 6-1,5/S - Reducing bridge

3213250

<https://www.phoenixcontact.com/nl/products/3213250>



Reducing bridge, pitch: 8 mm, number of positions: 2, nominal current: 32 A, length: 30 mm, color: red

 Max. current carrying capacity: 24 A

---

## D-PT 6-QUATTRO - End cover

3212963

<https://www.phoenixcontact.com/nl/products/3212963>

End cover, depth: 36 mm, width: 2.2 mm, height: 90.5 mm, color: gray



# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## WS PT 6 - Warning label

1029029

<https://www.phoenixcontact.com/nl/products/1029029>



Warning label, yellow/black, labeled: Lightning flash, mounting type: plug in, for terminal block width: 8.2 mm

---

## LPS-8/E - Service connector

3270560

<https://www.phoenixcontact.com/nl/products/3270560>



Service connector, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: red

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## LPS-8 - Service connector

3270561

<https://www.phoenixcontact.com/nl/products/3270561>



Service connector, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: red

---

## LPO 6/E - Pick-off plug

3270525

<https://www.phoenixcontact.com/nl/products/3270525>



Pick-off plug, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: gray

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## LPO 6 - Pick-off plug

3270526

<https://www.phoenixcontact.com/nl/products/3270526>



Pick-off plug, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: gray

---

## NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/nl/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>



## NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/nl/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: silver-colored

---

## NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/nl/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>



## NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/nl/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



---

## NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/nl/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, galvanized, white passivated, Standard profile, color: silver-colored

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>



## NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/nl/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver-colored

---

## NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/nl/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>



## NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/nl/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



---

## NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/nl/products/1201798>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver-colored

# PT 6-QUATTRO - Feed-through terminal block


3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## ZB 8:UNBEDRUCKT - Zack marker strip

1052002

<https://www.phoenixcontact.com/nl/products/1052002>




Zack marker strip, Strip, white, unmarked, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 10, text field height: 10.5 mm, text field width: 8.15 mm

---

## ZB 8 CUS - Zack marker strip

0825011

<https://www.phoenixcontact.com/nl/products/0825011>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, Number of individual labels: 10, text field height: 8.15 mm, text field width: 10.5 mm

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## UC-TM 8 - Marker for terminal blocks

0818072

<https://www.phoenixcontact.com/nl/products/0818072>



Marker for terminal blocks, Sheet, white, unmarked, can be labeled with: BLUEMARK E.CARD, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 56, text field height: 10.5 mm, text field width: 7.6 mm

---

## UC-TM 8 CUS - Marker for terminal blocks

0824597

<https://www.phoenixcontact.com/nl/products/0824597>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, Number of individual labels: 56, text field height: 10.5 mm, text field width: 7.6 mm

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## UCT-TM 8 - Marker for terminal blocks

0828740

<https://www.phoenixcontact.com/nl/products/0828740>



Marker for terminal blocks, Sheet, white, unmarked, can be labeled with: BLUEMARK E.CARD, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME 2.0, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, TOPMARK NEO, TOPMARK LASER, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 42, text field height: 10.5 mm, text field width: 7.6 mm

---

## UCT-TM 8 CUS - Marker for terminal blocks

0829616

<https://www.phoenixcontact.com/nl/products/0829616>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, Number of individual labels: 42, text field height: 10.5 mm, text field width: 7.6 mm

# PT 6-QUATTRO - Feed-through terminal block


3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## ZB 8,LGS:L1-N,PE - Marker for terminal blocks

1052413

<https://www.phoenixcontact.com/nl/products/1052413>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 10, text field height: 10.5 mm, text field width: 8.15 mm

---

## ZBF 8:UNBEDRUCKT - Zack Marker strip, flat

0808781

<https://www.phoenixcontact.com/nl/products/0808781>



Zack Marker strip, flat, Strip, white, unmarked, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 8 mm, Number of individual labels: 10, text field height: 8.15 mm, text field width: 5.15 mm

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## ZBF 8 CUS - Zack Marker strip, flat

0825030

<https://www.phoenixcontact.com/nl/products/0825030>



Zack Marker strip, flat, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8 mm, Number of individual labels: 10, text field height: 8.15 mm, text field width: 5.15 mm

---

## UC-TMF 8 - Marker for terminal blocks

0818137

<https://www.phoenixcontact.com/nl/products/0818137>



Marker for terminal blocks, Sheet, white, unmarked, can be labeled with: BLUEMARK E.CARD, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 56, text field height: 5.1 mm, text field width: 7.6 mm

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## UC-TMF 8 CUS - Marker for terminal blocks

0824654

<https://www.phoenixcontact.com/nl/products/0824654>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8.2 mm, Number of individual labels: 56, text field height: 5.1 mm, text field width: 7.6 mm

---

## UCT-TMF 8 - Marker for terminal blocks

0828748

<https://www.phoenixcontact.com/nl/products/0828748>



Marker for terminal blocks, Sheet, white, unmarked, can be labeled with: BLUEMARK E.CARD, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME 2.0, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, TOPMARK NEO, TOPMARK LASER, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 42, text field height: 4.7 mm, text field width: 7.4 mm

## PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>



## UCT-TMF 8 CUS - Marker for terminal blocks

0829672

<https://www.phoenixcontact.com/nl/products/0829672>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8.2 mm, Number of individual labels: 42, text field height: 4.7 mm, text field width: 7.4 mm

---

## MPS-MT - Test plug

0201744

<https://www.phoenixcontact.com/nl/products/0201744>



Test plug, with solder connection up to 1 mm<sup>2</sup> conductor cross-section, number of positions: 1, color: gray

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## MPS-IH WH - Insulating sleeve

0201663

<https://www.phoenixcontact.com/nl/products/0201663>

Insulating sleeve, color: white



---

## MPS-IH RD - Insulating sleeve

0201676

<https://www.phoenixcontact.com/nl/products/0201676>

Insulating sleeve, color: red



# PT 6-QUATTRO - Feed-through terminal block



3212934


<https://www.phoenixcontact.com/nl/products/3212934>

## MPS-IH BU - Insulating sleeve

0201689

<https://www.phoenixcontact.com/nl/products/0201689>

Insulating sleeve, color: blue



---

## MPS-IH YE - Insulating sleeve

0201692

<https://www.phoenixcontact.com/nl/products/0201692>

Insulating sleeve, color: yellow



# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## MPS-IH GN - Insulating sleeve

0201702

<https://www.phoenixcontact.com/nl/products/0201702>

Insulating sleeve, color: green



---

## MPS-IH GY - Insulating sleeve

0201728

<https://www.phoenixcontact.com/nl/products/0201728>

Insulating sleeve, color: gray



# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>



## MPS-IH BK - Insulating sleeve

0201731

<https://www.phoenixcontact.com/nl/products/0201731>

Insulating sleeve, color: black



---

## PAI-4-FIX BU - Test adapter

3032729

<https://www.phoenixcontact.com/nl/products/3032729>

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: blue



# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>



## PAI-4-FIX OG - Test adapter

3034455

<https://www.phoenixcontact.com/nl/products/3034455>



4 mm test adapter, for terminal blocks with 8.2 mm pitch

---

## PAI-4-FIX YE - Test adapter

3032745

<https://www.phoenixcontact.com/nl/products/3032745>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: yellow

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## PAI-4-FIX RD - Test adapter

3032732

<https://www.phoenixcontact.com/nl/products/3032732>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: red

---

## PAI-4-FIX GN - Test adapter

3032758

<https://www.phoenixcontact.com/nl/products/3032758>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: green

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## PAI-4-FIX BK - Test adapter

3032774

<https://www.phoenixcontact.com/nl/products/3032774>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: black

---

## PAI-4-FIX GY - Test adapter

3032790

<https://www.phoenixcontact.com/nl/products/3032790>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: gray

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## PAI-4-FIX VT - Test adapter

3032761

<https://www.phoenixcontact.com/nl/products/3032761>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: violet

---

## PAI-4-FIX BN - Test adapter

3032787

<https://www.phoenixcontact.com/nl/products/3032787>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: brown

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## PAI-4-FIX WH - Test adapter

3032797

<https://www.phoenixcontact.com/nl/products/3032797>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: white

---

## PAIS-4-FIX GY - Test adapter

3032791

<https://www.phoenixcontact.com/nl/products/3032791>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: gray

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## PAIS-4-FIX BK - Test adapter

3032792

<https://www.phoenixcontact.com/nl/products/3032792>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: black

---

## PAIS-4-FIX RD - Test adapter

3032793

<https://www.phoenixcontact.com/nl/products/3032793>



Test adapter, Do not plug in while the power is connected, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: red

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## PAIS-4-FIX BU - Test adapter

3032798

<https://www.phoenixcontact.com/nl/products/3032798>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: blue

---

## PAIS-4-FIX YE - Test adapter

3032799

<https://www.phoenixcontact.com/nl/products/3032799>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: yellow

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## PAIS-4-FIX GN - Test adapter

3032801

<https://www.phoenixcontact.com/nl/products/3032801>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: green

---

## PAIS-4-FIX VT - Test adapter

3032802

<https://www.phoenixcontact.com/nl/products/3032802>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: violet

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>



## PS-8 - Test plug

3031005

<https://www.phoenixcontact.com/nl/products/3031005>



Test plug, Modular test plug, number of positions: 1, color: red

---

## DP PS-8 - Spacer plate

3036741

<https://www.phoenixcontact.com/nl/products/3036741>



Spacer plate, depth: 29 mm, width: 8.2 mm, height: 22.4 mm, number of positions: 1, color: red

# PT 6-QUATTRO - Feed-through terminal block

3212934

<https://www.phoenixcontact.com/nl/products/3212934>



## PS-8/2,3MM RD - Test plug

3048564

<https://www.phoenixcontact.com/nl/products/3048564>



Test plug, number of positions: 1, color: red

---

## TMT (EX9,5)R - Marker for terminal blocks

0828295

<https://www.phoenixcontact.com/nl/products/0828295>



Marker for terminal blocks, Roll, white, unmarked, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: latching, snap into tall marker groove, for terminal block width: 30000 mm, Number of individual labels: 1, roll length: 30 m, text field height: 9.5 mm, text field width: 50000 mm

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## US-TM 100 - Marker for terminal blocks

0829255

<https://www.phoenixcontact.com/nl/products/0829255>



Marker for terminal blocks, Card, white, unmarked, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, THERMOMARK PRIME 2.0, mounting type: latching, Number of individual labels: 13, text field height: 9.8 mm, text field width: 104 mm

---

## SZF 2-0,8X4,0 - Screwdriver

1204520

<https://www.phoenixcontact.com/nl/products/1204520>



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.8 x 4.0 x 100 mm, 2-component grip, with non-slip grip

# PT 6-QUATTRO - Feed-through terminal block



3212934

<https://www.phoenixcontact.com/nl/products/3212934>

## PROJECT COMPLETE - Software

1050453

<https://www.phoenixcontact.com/nl/products/1050453>



Intuitive planning and marking software for configuring terminal strips and for professional marking of marking materials for terminal blocks, conductors, cables, devices, and systems. The software is available for download

---

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT B.V.  
Hengelder 56 6902 PA Zevenaar  
Postbus 246 6900 AE Zevenaar  
(0316) 59 17 20  
[sales@phoenixcontact.nl](mailto:sales@phoenixcontact.nl)